

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1. (currently amended) A disk storage device comprising:
 - an information storing disk;
 - a head for writing data to tracks on said disk and/or reading data from tracks on said disk;
 - a head-moving mechanism that moves said head in response to an input signal;
 - a head-position measuring circuit that generates a head-position signal representing a radial position of said head relative to said disk;
 - a current feedback amplifier;
 - a voltage feedback amplifier; and
 - a controller that is configured to:
 - generate a drive signal using a desired track-position signal and said head-position signal generated by said head-position measuring circuit,
 - set an upper limit on said drive signal,
 - monitor said head-position signal, or a signal derived from said head-position signal, to determine whether a malfunction condition exists, and
 - in the event of determining that a malfunction condition exists, causing said drive signal to be applied as an input to said voltage feedback amplifier and causing an output from said voltage feedback amplifier to provide said input signal to said head-moving mechanism, or
 - in the event of determining that a malfunction condition does not exist, causing said drive signal to be applied as an input to said current feedback amplifier and causing an output from said [[voltage]] current feedback amplifier to provide said input signal to said head-moving mechanism.

2. (original) The disk storage device of claim 1 wherein said signal derived from said head-position signal includes one or more of a positioning error signal, a speed signal or a speed error signal.

3. (original) The disk storage device of claim 1 wherein said malfunction condition is due to defects in said disk or troubles in said head when said head is moved for seeking and tracking.

4. (original) The disk storage device of claim 1 wherein said malfunction condition is an instability of said head-position signal or said signal derived from said head-position signal.

5. (currently amended) A disk storage device comprising:
an information storing disk;
a head for writing data to tracks on said disk and/or reading data from tracks on said disk;
a head support mechanism supporting and moving said head in response to an input signal;
a voice-coil motor for driving said head support mechanism;
a head-position measuring circuit for measuring a radial position of said head relative to said disk;
a controller that calculates a drive signal on the basis of a desired track-position signal and a measured head-position signal measured by said head-position measuring circuit and sends out said drive signal for positioning said head at a position corresponding to a desired track; and
a drive circuit driven by said drive signal for positioning said head at a position corresponding to said desired track by driving said voice-coil motor;
wherein:
said drive circuit includes a current feedback amplifier and a voltage feedback amplifier that are capable of being used selectively,

said controller is provided with a speed limiter for limiting the speed of said head to a predetermined maximum speed, and

said controller is configured to

in the event of determining that a malfunction condition exists, causing said drive signal to be applied as an input to said voltage feedback amplifier and causing an output from said voltage feedback amplifier to provide said input signal to said head support mechanism, or

in the event of determining that a malfunction condition does not exist, causing said drive signal to be applied as an input to said current feedback amplifier and causing an output from said current feedback amplifier to provide said input signal to said head support mechanism.

~~said voltage feedback amplifier of said drive circuit is used when said head position signal is unstable, and said current feedback amplifier of said drive circuit is used when said head position signal is a normal signal during seeking and tracking operations.~~

6. (currently amended) The disk storage device of claim 5 wherein said malfunction condition appears ~~unstable head position signal is obtained~~ immediately after said disk storage device is connected to a power supply.

7. (currently amended) A disk storage device comprising:
an information storing disk;
a head for writing data to tracks on said disk and/or reading data from tracks on said disk;
a head support mechanism supporting and moving said head in response to an input signal;
a voice-coil motor for driving said head support mechanism;
a head-position measuring circuit for measuring a radial positioning of said head relative to said disk;
a controller that calculates a drive signal on the basis of a desired track-positioning signal and a measured head-position signal measured by said head-positioning

measuring circuit and sends out said drive signal to positioning said head at a position corresponding to a desired track; and

a drive circuit driven by said drive signal for positioning said head at a position corresponding to said desired track by driving said voice-coil motor;

wherein:

said drive circuit includes a current feedback amplifier and a voltage feedback amplifier that are capable of being used selectively,

said controller is provided with a speed limiter for limiting the speed of said head to a predetermined maximum speed, and

said controller is configured to

in the event of determining that said head-position signal is a malfunction signal due to defects in said disk or troubles in said head when said head is moved for seeking and tracking, causing said drive signal to be applied as an input to said voltage feedback amplifier and causing an output from said voltage feedback amplifier to provide said input signal to said head support mechanism, or

in the event of determining that said head-position signal is a normal signal, causing said drive signal to be applied as an input to said current feedback amplifier and causing an output from said current feedback amplifier to provide said input signal to said head support mechanism.

~~said current feedback amplifier of said drive circuit is used when said head position signal is a normal signal, and said voltage feedback amplifier of said drive circuit is used when said head position signal is a malfunction signal due to defects in said disk or troubles in said head when said head is moved for seeking and tracking.~~

8. (currently amended) The disk storage device of claim 5, 6, or 7 wherein said speed limiter is saturated with a value obtained by dividing $\frac{1}{a}$ a product of multiplication of $\frac{1}{a}$ said predetermined maximum speed (V_{\max} (m/s)) and a counter electromotive voltage constant (k_f (V/(m/s))) of said voice-coil motor by $\frac{1}{a}$ a gain (K_v (V/V)) of said voltage feedback amplifier.

9. (original) The disk storage device of claim 1, 5, 6, or 7 wherein said controller includes:

a speed determining unit that provides a speed signal indicating said speed of said head by differentiating said head-position signal provided by said head-positioning measuring circuit;

a desired speed determining unit that generates a desired speed signal on said basis of said head-position signal provided by said head-positioning measuring circuit and said desired track-positioning signal; and

a subtractor that generates a speed deviation signal by subtracting said output signal of said desired speed determining unit from said output signal of said speed determining unit.

10. (original) The disk storage device of claim 1, 5, 6, or 7 wherein said information storage disk is a magnetic disk.

11. (original) The disk storage device of claim 1, 5, 6, or 7 wherein said head both reads information from said disk and writes information to said disk.